

PONNDORF

pump hose

- All Ponndorf pump hose is precision molded to optimize performance with Ponndorf hose pumps



PX series



PDX series



PD series



PK series

Specifications & Ordering Information

| Pump series | Max flow m ³ /hr (GPM) | Max pressure bar (psig) | Max suction m (ft) of H ₂ O | Ponndorf pump hose formulation | | | | |
|-------------|--------------------------------------|----------------------------|-------------------------------------------|--------------------------------|---------------------------|----------------|----------|----------------------|
| | | | | Natural rubber | Food-grade natural rubber | Neoprene | Hypalon | Food-grade Ponnprene |
| PX 10 | 0.15 (0.66) | 2 (30) | 7 (23) | VA-61008 | VA-61011 | VA-61009 | VA-61010 | — |
| PX 10/2 | 0.25 (1.1) | 2 (30) | 7 (23) | VA-61008 | VA-61011 | VA-61009 | VA-61010 | — |
| PX 15 | 0.5 (2.2) | 2 (30) | 7 (23) | VA-61108 | VA-61111 | VA-61109 | VA-61110 | — |
| PX 15/2 | 0.95 (4.2) | 2 (30) | 7 (23) | VA-61108 | VA-61111 | VA-61109 | VA-61110 | — |
| PX 27 | 2.2 (9.7) | 2 (30) | 7 (23) | VA-61208 | VA-61211 | VA-61209 | VA-61210 | — |
| PX 27/2 | 5.0 (22) | 2 (30) | 7 (23) | VA-61208 | VA-61211 | VA-61209 | VA-61210 | — |
| PX 35 | 6.0 (26) | 2 (30) | 7 (23) | VA-61308 | VA-61311 | VA-61309 | VA-61310 | — |
| PX 35/2 | 11.5 (51) | 2 (30) | 7 (23) | VA-61308 | VA-61311 | VA-61309 | VA-61310 | — |
| PX 50 | 12.5 (55) | 2 (30) | 7 (23) | VA-61408 | VA-61411 | VA-61409 | VA-61410 | — |
| PX 50/2 | 24.5 (108) | 2 (30) | 7 (23) | VA-61408 | VA-61411 | VA-61409 | VA-61410 | — |
| PDX 19 | 0.5 (2.2) | 2 (30) | 7 (23) | — | — | — | — | VA-61808 |
| PDX 19/2 | 0.85 (3.7) | 2 (30) | 7 (23) | — | — | — | — | VA-61808 |
| PDX 30 | 2.7 (12) | 2 (30) | 7 (23) | — | — | — | — | VA-61908 |
| PDX 30/2 | 4.5 (20) | 2 (30) | 7 (23) | — | — | — | — | VA-61908 |
| PDX 35 | 4 (18) | 2 (30) | 7 (23) | — | — | — | — | VA-62008 |
| PDX 35/2 | 6.7 (30) | 2 (30) | 7 (23) | — | — | — | — | VA-62008 |
| PD 15 | 0.5 (2.2) | 4 (60) | 8 (26) | — | — | — | — | VA-61508 |
| PD 15/2 | 0.95 (4.2) | 4 (60) | 8 (26) | — | — | — | — | VA-61508 |
| PD 27 | 2.5 (11) | 4 (60) | 8 (26) | — | — | — | — | VA-61608 |
| PD 27/2 | 4.8 (21) | 4 (60) | 8 (26) | — | — | — | — | VA-61608 |
| PD 35 | 5.5 (24.2) | 4 (60) | 8 (26) | — | — | — | — | VA-61708 |
| PD 35/2 | 9.5 (42) | 4 (60) | 8 (26) | — | — | — | — | VA-61708 |
| Pump series | Max flow m ³ /hr (GPM) | Max pressure bar (psig) | Max suction m (ft) of H ₂ O | Ponndorf pump hose formulation | | | | |
| | | | | Natural rubber | EPDM | Food grade NBR | — | |
| PK 15 | 0.7 (3) | 5 (220) | 8 (26) | VA-62509 | VA-62508 | VA-62509 | — | |
| PK 25 | 2.1 (9.2) | 5 (220) | 8 (26) | VA-62607 | VA-62608 | VA-62609 | — | |
| PK 40 | 7.7 (34) | 5 (220) | 8 (26) | VA-62707 | VA-62708 | VA-62709 | — | |
| PK 50 | 15.5 (68) | 5 (220) | 8 (26) | VA-62807 | VA-62808 | VA-62809 | — | |
| PK 65 | 32 (140) | 5 (220) | 8 (26) | VA-62924 | VA-62925 | VA-62926 | — | |